



5	BUSHING	PTFE
4	X-RING	NBR
3	STEM	SS410
2	DISC	FDA EPDM COATED
1	BODY	DI
NO. PARTS NAME		MATERIAL
TEST PRESSURE		SHELL SEAL
	HYDROSTATIC	225 PSI 165 PSI
	AIR	
STANDARD	DESIGN CODE	ANSI 150#

Unit: inch

SIZE	A	B	C	E	F	H	I	K	L	B1XB1	J	N	4-Ød1
2	1.97	2.25	2.37	0.63	0.31	4.69	2.48	1.18	3.24	0.43	3.54	2.76	0.39
2.5	2.40	2.72	2.87	0.63	0.31	4.92	2.70	1.18	3.81	0.43	3.54	2.76	0.39
3	3.07	3.34	3.50	0.63	0.31	5.18	3.15	1.18	3.81	0.43	3.54	2.76	0.39
4	3.98	4.33	4.50	0.63	0.38	5.94	3.70	1.18	4.56	0.43	3.54	2.76	0.39
5	5.00	5.39	5.56	0.63	0.38	6.75	4.25	1.18	5.81	0.55	3.54	2.76	0.39
6	5.91	6.46	6.63	0.63	0.38	7.20	4.84	1.18	5.81	0.55	3.54	2.76	0.39
8	7.95	8.44	8.63	0.75	0.44	8.09	5.88	1.57	6.25	0.67	4.92	4.02	0.47
10	9.96	10.56	10.75	0.75	0.50	9.84	7.32	1.57	6.25	0.87	4.92	4.02	0.47
12	11.96	12.53	12.75	0.75	0.50	10.83	8.39	1.57	6.44	0.87	4.92	4.02	0.47

Drawing Title: BFV-NSF-GVEL-BL Buried Service Outdoor Rated	 INDUSTRIAL CHOICE	Phone # 541-564-7636	Date 12/28/2018
		Fax # 541-564-6522	Drafted by MD