



# INDUSTRIAL CHOICE



## INDUSTRIAL CHOICE DURAGLIDE TANK TRUCK-XFLEX CORRUGATED LIGHTWEIGHT TANK TRUCK HOSE W/UHMW COVER



*DuraGlide Tank-Truck-XFlex is an engineered hose, specially compounded to make it Durable, Easy to Drag, Flexible & Lightweight. It pulls a Full Vacuum/Suction (30" Hg). Handles gasoline grades to 50% aromatic, Bio Fuels to B20 such as Biodiesel, Biogasoline as well as most refined oils.*

Wire Helix provides a path to conduct a static electrical charge to ground.

*Applications: Gasolines up to 50% Aromatics, Diesel, Oils Biofuels to B20*

*Use on Transport Trucks, Trailers and in-Plant loading and Transferring!*

Item Number	ID (Inch)	OD (Inch)	WPSI	Bend Radius	Weight (lbs/ft.)	Notes
<a href="#">DuraGlide-Tank-Xflex-1.5RD</a>	1.5	2.02	250	1.5	0.760	
<a href="#">DuraGlide-Tank-Xflex-2RD</a>	2	2.64	200	2	1.060	
<a href="#">DuraGlide-Tank-Xflex-3RD</a>	3	3.65	200	3	1.730	
<a href="#">DuraGlide-Tank-Xflex-4RD</a>	4	4.65	200	4	2.450	

Note! Dimensions and weights can vary slightly and are approximate!

Tube: Black Nitrile Rubber blend, antistatic (R<108Ω)

Cover: Red Corrugated Nitrile Rubber W/UHMW outer liner for super abrasion resistance.

Reinforcement: Multiple Ply Textile Spirals W/dual helix wire.

Temperatures: -40F to 212F. Note PSI ratings at 78F as Temp's go up Wpsi goes down.

Branded: Industrial Choice DuraGlide Tank Truck Xflex 200wp

**Warning:** The user of this product is responsible for determining if the hose is suitable for the application!

**Warning:** Attaching hose ends W/bands or clamps may reduce hose assembly WPSI. See Nahad Guidelines.

Compare to: Contitech Plicord Extremeflex Petroleum, TuderTechnica GlideTech Drop Hose