



# INDUSTRIAL CHOICE



## INDUSTRIAL CHOICE EXTREMEFLEX LT CORRUGATED LIGHTWEIGHT TANK TRUCK HOSE



**EXTREMEFLEX LT is an engineered hose, specially compounded to make it Extremely Flexible & Lightweight. Pulls a Full Vacuum/Suction (30"Hg). Handles gasoline grades to 50% aromatic, Bio Fuels to B20 such as Biodiesel, Biogasoline as well as most refined oils.**

Wire Helix provides a path to conduct a static electrical charge to ground.

**Applications: Gasolines up to 50% Aromatics, Diesel, Oils Biofuels to B20**

**Use on Transport Trucks, Trailers, in-Plant loading and Transferring!**

Item Number	ID (Inch)	OD (Inch)	WPSI	Bend Radius	Weight (lbs/ft.)	Notes
EXTREMEFLEX-LT-2	2	2.39	150	2	0.900	
EXTREMEFLEX-LT-3	3	3.44	150	3	1.510	
EXTREMEFLEX-LT-4	4	4.48	150	4	2.280	

Note! Dimensions and weights can vary slightly and are approximate!

Tube: Black Nitrile Rubber blend.

Cover: Red Corrugated Nitrile Rubber blend offers abrasion resistance.

Reinforcement: Multiple Ply Textile Spirals W/dual helix wire.

Temperatures: -40F to 180F at 150wpsi. Higher temps to 200F achieved at lower psi

Branded: Industrial Choice Extremeflex Lightweight Tank Truck Hose 150wp -40F-180F

**Warning:** The user of this product is responsible for determining if the hose is suitable for the application!

**Warning:** Attaching hose ends W/bands or clamps may reduce hose assembly WPSI. See Nahad Guidelines.

Compare to: Thermoid Flex Devil, Parker SWC316R, Gates Megaflex, Contitech Plicord E.F