



# INDUSTRIAL CHOICE



## INDUSTRIAL CHOICE UTLFH URATUFF-URETHANE LINED FLEX HOSE Thermoplastic Urethane Lined Material Handling Hose



*Designed for dry abrasive applications: Ex. Dry Fertilizer, Corn starch, Plastic pellets, Airline seeder lines, Fly Ash, Lime, Dry Cement powder, Powders, Silica, Sand, Rocks Blasting Soda, Shot Blast, Industrial Vacuum Equipment, abrasive food products Etc.*

Item Number	ID (Inch)	OD (Inch)	WPSI @ 68F/104F	VAC IN. 68F/104F	Weight (lbs/ft.)	Min. Bend Radius	Notes
<u>ICH-UTLFH-2</u>	2"	2.41"	40/20	29/28	0.60	3"	
<u>ICH-UTLFH-2.5</u>	2.5"	3.08"	40/20	29/28	0.80	3.5"	
<u>ICH-UTLFH-3</u>	3"	3.64"	40/20	29/28	1.190	4"	
<u>ICH-UTLFH-4</u>	4"	4.77"	35/18	29/28	1.490	6"	
<u>ICH-UTLFH-5</u>	5"	5.75"	35/18	29/28	2.420	10"	
<u>ICH-UTLFH-6</u>	6"	6.82"	30/15	28/25	3.510	12"	
<u>ICH-UTLFH-8</u>	8"	9.20"	30/15	28/25	5.920	18"	

**Note! Dimensions and weights can vary slightly and are approximate!**

Tube: Thick FDA/NSF Approved Polyurethane Abrasion Resistant Liner

Cover: Black Corrugated PVC

Reinforcement: Rigid PVC Helical

Temperature Service Range; -40F to 150F

Branded: No Branding on Hose only on Label.

Warnings: The user of this product is responsible for determining if the hose is suitable for the application!

Not for Food Grade applications.