



INDUSTRIAL CHOICE



KWIKFORM-Multipurpose-Oil Resistant



KWIKFORM Greco style hose. Super flexible & forms great for tight confined spaces
Multi-purpose NBR Nitrile Rubber tube and cover handles oils and refined fuels (B20)
75WPSI -30F to 212F, 29IN vac.

Applications: Oil suction, low pressure return, fuel fill connections. radiator, coolant.

ra Number	ID (Inch)	OD (Inch)	Bend Radius	WP (PSI)	Burst (PSI)	Weight (lbs/ft)	Notes
KWIKFORM-MPO-1.00	1.00"	1.49"	1.90"	75	325	0.54	
KWIKFORM-MPO-1.13	1.125"	1.60"	2.30"	75	325	0.56	
KWIKFORM-MPO-1.25	1.25"	1.80"	2.70"	75	300	0.59	
KWIKFORM-MPO-1.38	1.375"	1.90"	3.30"	75	300	0.68	
KWIKFORM-MPO-1.50	1.50"	2.00"	3.40"	75	300	0.75	
KWIKFORM-MPO-1.75	1.75"	2.32"	4.05"	75	300	0.80	
KWIKFORM-MPO-2.00	2.00"	2.65"	4.60"	75	300	1.13	
KWIKFORM-MPO-2.38	2.375"	3.15"	7.50"	75	300	1.31	
KWIKFORM-MPO-2.50	2.50"	3.20"	7.85"	75	300	1.38	
KWIKFORM-MPO-2.75	2.75"	3.475"	8.75"	75	300	1.65	
KWIKFORM-MPO-3.00	3.00"	3.72"	9.60"	75	300	1.78	

Note! Dimensions, weights can vary slightly & are approximate! WPSI is based on Temp @ 70deg F.

Tube: Black Nitrile Rubber: Handles Oils, Gasoline, Ethanol, Bio-Diesel to B20

Cover: Black Chloroprene Rubber

Temperature Ranges: Deg.-40F to 140F

Warning: The user of this product is responsible for determining if the hose is suitable for the application!

Compare to: Parker 7219 E-Z FORM.