



INDUSTRIAL CHOICE



INDUSTRIAL CHOICE WATER-SUCTION-HD300

WATER-LIGHT CHEMICAL HEAVY DUTY 300WPSI SUCTION-DISCHARGE HOSE



Applications: Water Suction & 300WPSI Discharge, Fire trucks, Brush Trucks, Light Water based Chemicals Ex. Fertilizer, Herbicides, Alkalies, Glycols, Brine, Ozone See Chemical Chart -40F to 212F

Item	ID	OD	WPSI	BPSI	Bend	Vac	Weight	Notes
<u>Number</u>	<u>(Inch)</u>	<u>(Inch)</u>			<u>Radius</u>	<u>(In/HG)</u>	<u>(lbs./ft.)</u>	
Water-Suction-HD300-1.5	1.5"	1.99"	300	1100	6.5"	29	.075lbs	
Water-Suction-HD300-2	2"	2.50"	300	1000	8"	29	0.96lbs	
Water-Suction-HD300-2.5	2.5"	3.04"	300	930	10"	29	1.40lbs	
Water-Suction-HD300-3	3"	3.55"	300	900	12"	29	1.72lbs	
Water-Suction-HD-300-4	4"	4.55"	300	900	16"	29	2.35lbs	

Tube: SBR Rubber Black

Cover: SBR Rubber Black

Reinforcement: 2 x Multiple Ply Textile Spirals. Steel wire Helical.

Temperature Range: -40F to +212F

Branded: Industrial Choice Water S & D 300PSI W.P.

Note! WPSI & Bend Radius are calculated at 70deg F. As Temperatures go up WPSI goes down & bend radius increases. Approx. a 10deg increase = -10% wpsi & bend radius +10%.

Compare to: Parker 7325, Altagoma T223AA